



KWC-No.	Finish
26.156.213.000	all chrome
AD 150 +/- 15 mm, A 300, with hand shower and hose	

Shower system Thermostatic mixer

Shower system KWC ONO

- EcoProtect - water-saving device
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- the water-bearing sliding wall bar can be shortened to any individual length as required
- Swiveling bracket, shower head with ball joint
- SkinProtect - Safety stop prevents scalding
- Turning handle to control flow and for diverter
- KWC ball joint bracket, elevation adjustment lockable
- Tube diameter 20 mm
- Intrinsicly safe against backflow
- Easy to install on existing connections
- Thermostatic precision control unit
 - constant water temperature (even when mains pressure fluctuates)
 - fast response
- Concealed wall connections 1/2" x 3/4", without shut-off valve L 46 eccentric 7.5 mm
- Scope of delivery:
 - Thermostat incl. wall connections with outlet (top) for water-bearing sliding wall bar
 - Hand shower KWC ELY mono 26.000.120.000
 - Shower hose 1800 mm, plastic 26.001.014.000
 - Shower head KWC PIATTO R240
 - Sliding wall bar kit 26.004.003.000
 - Shower guide rod holder (top), for connecting guide rod and spray arm