## KWC ONO touch light PRO





265 97 944 256 900 235 235 2000 3/8" 74 3/8"



KBCULTURE AWARD 2012

KWC-No.

inish

## 10.651.022.000FL

all chrome

A 220, flexible connection hoses, mains receiver

## Kitchen with LED-technology

IntelligentControl - electronic control

- touch light PRO technology
- touch'n'flow 1-2-3
- 3 preset temperatures and flow rates
- Microprocessor-control
- touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
- with cleaning programme
- duration of water flow safety indication: switch off automatically after 10 minutes
- temperature limit can be adjusted
- hot water disinfection (5 minutes) can be adjusted
- can be restored to factory settings
- Swivel spout 360°
- Neoperl® SLIM®
- OptimalSpace ample space for washing or working
- touch light PRO control unit, maintenance-free
- up-to-date microprocessor and drive technology
- tried-and-tested valve technology
- incl. installation materials
- designed for wired connection to 1 operating unit (standard)
  , wireless connection to 1 operating unit (optional)
- Flexible connection hoses ¾"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm
- Scope of delivery:
- Mains receiver 100-240 V / operating voltage 15 V / cable length 900 mm
- Control unit and wired operating unit / cable length 2000 mm
- To be ordered separately (optional or if necessary):
- Extension set 1500 mm Z.536.352, comprising: stainless steel hose 1500 mm, 3" x 3", double nipple, sealing material
- KWC ONO touch light PRO wireless operating unit

## Z.536.351.000

 Go to www.kwc.com for comprehensive information on planning, installation and operation, or get in touch with your KWC contact person.